



## Automotive Battery Cable

Australian Made

www.qvee.com.au



### DESCRIPTION

Australian manufactured, high density automotive battery cable with a plain copper conductor and the highest quality insulation. Designed for durability and reliability. Conforms to Australian Standard. RoHS Compliant.

### TECHNICAL SPECIFICATIONS

<b>Conductor</b>	• Plain Copper Conductor to AS1125
<b>Insulation</b>	• UV Stabilised V90 PVC to AS 3808:2000

<b>Voltage</b>	• AC 50V / DC 120V to AS/NZS 3000:2000
<b>Application</b>	• Battery & Starter Cable

Part No.	Roll Length	mm <sup>2</sup>	Amps	Colour
8BS30BK	30m	8 B&S (7.92mm <sup>2</sup> )	75 Amps	Black
8BS100BK	100m			
8BS30RD	30m	8 B&S (7.92mm <sup>2</sup> )	75 Amps	Red
8BS100RD	100m			
6BS30BK	30m	6 B&S (13.36mm <sup>2</sup> )	100 Amps	Black
6BS100BK	100m			
6BS30RD	30m	6 B&S (13.36mm <sup>2</sup> )	100 Amps	Red
6BS100RD	100m			
4BS30BK	30m	4 B&S (20.25mm <sup>2</sup> )	130 Amps	Black
4BS100BK	100m			
4BS30RD	30m	4 B&S (20.25mm <sup>2</sup> )	130 Amps	Red
4BS100RD	100m			
3BS30BK	30m	3 B&S (25.70mm <sup>2</sup> )	160 Amps	Black
3BS100BK	100m			
3BS30RD	30m	3 B&S (25.70mm <sup>2</sup> )	160 Amps	Red
3BS100RD	100m			
2BS30BK	30m	2 B&S (32.15mm <sup>2</sup> )	180 Amps	Black
2BS100BK	100m			

Part No.	Roll Length	mm <sup>2</sup>	Amps	Colour
2BS30RD	30m	2 B&S (32.15mm <sup>2</sup> )	180 Amps	Red
2BS100RD	100m			
1BS30BK	30m	1 B&S (39.55mm <sup>2</sup> )	200 Amps	Black
1BS100BK	100m			
1BS30RD	30m	1 B&S (39.55mm <sup>2</sup> )	200 Amps	Red
1BS100RD	100m			
0BS30BK	30m	0 B&S (49.50mm <sup>2</sup> )	240 Amps	Black
0BS100BK	100m			
0BS30RD	30m	0 B&S (49.50mm <sup>2</sup> )	240 Amps	Red
0BS100RD	100m			
00BS30BK	30m	00 B&S (64.30mm <sup>2</sup> )	290 Amps	Black
00BS100BK	100m			
00BS30RD	30m	00 B&S (64.30mm <sup>2</sup> )	290 Amps	Red
00BS100RD	100m			
000BS30BK	30m	000 B&S (85.00mm <sup>2</sup> )	330 Amps	Black
000BS100BK	100m			
000BS30RD	30m	000 B&S (85.00mm <sup>2</sup> )	330 Amps	Red
000BS100RD	100m			