



DTHD Series Housing

Sold Individually



www.te.com

www.qvee.com.au

DESCRIPTION

Deutsch DTHD Series of environmentally sealed connectors are designed specifically for cable to cable applications on the engine or transmission, under the hood, on the chassis or in the cab. Where signal level circuits in harsh environmental conditions, where even a small degradation in connection may be critical, the Deutsch DTHD Series heavy duty connectors will provide reliability and performance.



TECHNICAL SPECIFICATIONS

Operating Temperature	• -55° C to 125° C	Circuit Application	• Power & signal
Operating Voltage	• 250V DC	Durability Resistance	• No damage after 100 re-engagement
Connector System	• Wire to wire	Dielectric Withstand	• Less than 2mA @ 1500V AC
Body Material	• PEI (Polyetherimide)	Insulation Resistance	• 1000 Megaohms min @ 25° C
Primary Locking Feature	• Integrated in housing	Moisture Resistance	• 3 feet immersion with proper wiring
Cable Exit Angle	• 180°	Vibration Resistance	• No mechanical / physical damage @ 20Gs rms at 10 to 2000Hz
IP Rating	• IP68 rated		

PART NUMBERS

Part Number.	Dimensions (mm)	Amperage	Terminal Size	Description
DTHD04-1-12P	• 18.03 W x 21.59 H x 52.53 L	• 25 Amp	• P12/1 (5mm auto)	• 25 Amps DTHD Series receptacle housing. Takes male pins
DTHD06-1-12S	• 14.48 W x 19.58 H x 38.05 L		• S12/1 (5mm auto)	• 25 Amps DTHD Series plug housing. Takes female sockets
DTHD04-1-8P	• 26.54 W x 29.72 H x 52.53 L	• 60 Amp	• P8/1 (8 B&S)	• 60 Amps DTHD Series receptacle housing. Takes male pins
DTHD06-1-8S	• 22.23 W x 27.33 H x 38.05 L		• S8/1 (8 B&S)	• 60 Amps DTHD Series plug housing. Takes female sockets
DTHD04-1-4P	• 26.54 W x 29.72 H x 52.53 L	• 100 Amp	• P4/1 (6 B&S)	• 100 Amps DTHD Series receptacle housing. Takes male pins
DTHD06-1-4S	• 22.23 W x 27.33 H x 38.05 L		• S4/1 (6 B&S)	• 100 Amps DTHD Series plug housing. Takes female sockets