



www.te.com

DT Series Housing with Heatshrink End

Sold Individually

www.qvee.com.au




DESCRIPTION

Deutsch DT Series housings are made from Thermoplastic and silicon rubber seals. Rated to IP68 specifications and has an operating temperature of between -55°C and 125°C. Perfect for harsh environmental applications where reliable signal circuits are critical to operation performance.

Connector System	• Wire to Wire	Cable Exit	• 180°
Sealable	• Yes	Body Material	• PA GF
Primary Locking Feature	• Intergrated in Housing	Mating Pin Diameter	• 1.5mm
Circuit Application	• Power & Signal	Contact Current Rating	• 13 Amps per Circuit
Voltage	• Up to 250V DC	Operating Temperature	• -55°C - 125°C
IP Rating	• IP68	Flammability	• UL Recognized, Standard UL-94

DT SERIES CONFIGURATIONS




DT04-2P
2 size 16



DT04-3P
3 size 16



DT04-4P
4 size 16



DT04-6P
6 size 16



DT04-8P
8 size 16



DT04-12P
12 size 16

PART NUMBERS

Part Number.	Dimensions (mm)	Centreline (mm)	Description
DT04-2P-E008	• 55.90 L x 17.02 H x 17.35 W	• 5.5	• 2 circuit DT receptacle housing with ridge to securely accept heatshrink
DT06-2S-E008	• 40.92 L x 16.56 H x 17.37 W		• 2 circuit DT series plug housing with ridge to securely accept heatshrink
DT04-3P-E008	• 55.40 L x 24.71 H x 21.14 W	• 8.7	• 3 circuit DT receptacle housing with ridge to securely accept heatshrink
DT06-3S-E008	• 40.67 L x 24.60 H x 20.23 W		• 3 circuit DT series plug housing with ridge to securely accept heatshrink
DT04-4P-E008	• 58.32 L x 19.74 H x 20.88 W	• 4.5	• 4 circuit DT receptacle housing with ridge to securely accept heatshrink
DT06-4S-E008	• 43.21 L x 19.74 H x 20.83 W		• 4 circuit DT series plug housing with ridge to securely accept heatshrink
DT04-6P-E008	• 58.19 L x 24.16 H x 20.83 W		• 6 circuit DT receptacle housing with ridge to securely accept heatshrink
DT06-6S-E008	• 43.21 L x 23.76 H x 20.68 W		• 6 circuit DT series plug housing with ridge to securely accept heatshrink
DT04-08PA-E008	• 59.00 L x 25.40 H x 36.45 W		• 8 circuit DT receptacle housing with ridge to securely accept heatshrink
DT06-08SA-E008	• 44.25 L x 22.15 H x 37.21 W		• 8 circuit DT series plug housing with ridge to securely accept heatshrink
DT04-12PA-E008	• 56.29 L x 22.25 H x 40.56 W		• 12 circuit DT receptacle housing with ridge to securely accept heatshrink
DT06-12SA-E008	• 43.38 L x 20.42 H x 40.56 W		• 12 circuit DT series plug housing with ridge to securely accept heatshrink