

Flexible Braided Sleeving

#ES

www.qvee.com.au

DESCRIPTION

Black flexible braided sleeving. Excellent protection from salt, oil and most fuel and solvents. Ideal for use on wiring looms where cables are connected to moving parts.

- Operating temperature range of -70°C to 120°C
- UL224 flammability rating method VW-1



Expands up to 300%
of initial diameter size.

TECHNICAL SPECIFICATIONS

Material	• Braided Polyethylene Terephthalate Monofilaments	Optimal Temperature	• -70°C to 120°C
Flammability	• UL224, method VW-1	Melting Point	• 250°C
Resistant	• Salt, oil, most fuels and solvents	Colour	• Black

PART NUMBERS

Part No.	Normal Diameter Size	Expanded Diameter Size	Roll Size	Description
ES0310	• 3mm	• 10mm	• Cut to length on request	• Black flexible braided sleeving with 10mm expanded diameter
ES0620	• 6mm	• 20mm		• Black flexible braided sleeving with 20mm expanded diameter
ES1230	• 12mm	• 30mm		• Black flexible braided sleeving with 30mm expanded diameter
ES2040	• 20mm	• 40mm		• Black flexible braided sleeving with 40mm expanded diameter
ES2560	• 25mm	• 60mm		• Black flexible braided sleeving with 60mm expanded diameter
ES3070	• 30mm	• 70mm		• Black flexible braided sleeving with 70mm expanded diameter