



Heatshrink Dispenser Boxes 3:1 Ratio

#QVHS

www.qvee.com.au



DESCRIPTION

The QVEE heatshrink tubing dispenser boxes contain a continuous length of 3:1 ratio heatshrink. The durable cardboard dispenser box is a great way to neatly store and use the QVEE heatshrink.

TECHNICAL SPECIFICATIONS

- Standard for extruded electrical tubing UL224

Material	• Polyolefin	Shrink Temperature	• 70°C
Temperature Range	• -55°C to 125°C	Longitudinal Shrinking	• Less than +/- 5%

PART NUMBERS

Part No.	Heatshrink Colour	Roll Size	Size As Supplied		Size After Recovered	
			I.D	Wall Thickness	I.D	Wall Thickness
QVHSB3BK	• Black	• 10.0m	• ≥ 3mm	• 0.25 +/- 0.05mm	• ≤ 1mm	• 0.55 +/- 0.1mm
QVHSB3RD	• Red	• 10.0m	• ≥ 3mm	• 0.25 +/- 0.05mm	• ≤ 1mm	• 0.55 +/- 0.1mm
QVHSB6BK	• Black	• 6.0m	• ≥ 6mm	• 0.25 +/- 0.05mm	• ≤ 2mm	• 0.65 +/- 0.1mm
QVHSB6RD	• Red	• 6.0m	• ≥ 6mm	• 0.25 +/- 0.05mm	• ≤ 2mm	• 0.65 +/- 0.1mm
QVHSB10BK	• Black	• 5.0m	• ≥ 9mm	• 0.28 +/- 0.05mm	• ≤ 3mm	• 0.75 +/- 0.15mm
QVHSB10RD	• Red	• 5.0m	• ≥ 9mm	• 0.28 +/- 0.05mm	• ≤ 3mm	• 0.75 +/- 0.15mm
QVHSB13BK	• Black	• 4.0m	• ≥ 12mm	• 0.28 +/- 0.05mm	• ≤ 4mm	• 0.75 +/- 0.15mm
QVHSB13RD	• Red	• 4.0m	• ≥ 12mm	• 0.28 +/- 0.05mm	• ≤ 4mm	• 0.75 +/- 0.15mm
QVHSB19BK	• Black	• 3.0m	• ≥ 18mm	• 0.3 +/- 0.05mm	• ≤ 6mm	• 0.85 +/- 0.15mm
QVHSB19RD	• Red	• 3.0m	• ≥ 18mm	• 0.3 +/- 0.05mm	• ≤ 6mm	• 0.85 +/- 0.15mm
QVHSB24BK	• Black	• 3.0m	• ≥ 24mm	• 0.3 +/- 0.05mm	• ≤ 8mm	• 1.0 +/- 0.2mm
QVHSB24RD	• Red	• 3.0m	• ≥ 24mm	• 0.3 +/- 0.05mm	• ≤ 8mm	• 1.0 +/- 0.2mm