

www.qvee.com.au



DTM Assortment Kit with Plastic Case

www.te.com

DESCRIPTION

#QVDTMKIT www.qvee.com.au



344 piece Deutsch DTM Series assortment kit.

and silicon rubber seals. Perfect for harsh environmental applications where reliable signal circuits are critical.

TECHNICAL SPECIFICATIONS

Operating Temperature	• -55° C to 125° C	Connector
Voltage	• Up to 250V DC	Primary L
Amperage	• 7.5 Amps per Circuit	Centreline
Nominal Voltage	• 12, 24, 42, 48, 80, 90, 125, 240 Volt	IP Rating
Moisture Resistance	• 3 Feet Immersion with Proper Wiring	Insulation
Flammability	• UL Recognized, Standard UL-94	Vibration
Dialectric Strength	• < 2 mA @ 1500V AC	vibration

Connector System	• Wire to Wire
Primary Locking Feature	 Integrated in Housing
Centreline (Pitch)	• 4.19mm
IP Rating	• IP68
Insulation Resistance	• 1000 Megaohms Min @ 25º C
Vibration Resistance	• No Mechanical / Physical Damage @ 20Gs rms at 10 to 2000Hz

COMPRISES

Part Number.	Qty	Description	Part Number.	Qty	Description
DTM04-2P	• 10	• 2 circuit DTM housing, takes pins	WM3P	• 3	• Pin wedge to suit DTM04-3P
DTM06-25	• 10	• 2 circuit DTM housing, takes sockets	WM35	• 3	 Socket wedge to suit DMT06-35
DTM04-3P	• 3	• 3 circuit DTM housing, takes pins	WM4P	• 3	• Pin wedge to suit DMT04-4P
DTM06-35	• 3	• 3 circuit DTM housing, takes sockets	WM4S	• 3	 Socket wedge to suit DTM06-4S
DTM04-4P	• 3	• 4 circuit DTM housing, takes pins	<i>WM6P</i>	• 3	• Pin wedge to suit DTM04-6P
DTM06-4S	• 3	• 4 circuit DTM housing, takes sockets	WM65	• 3	 Socket wedge to suit DTM06-65
DTM04-6P	• 3	• 6 circuit DTM housing, takes pins	WM8P	• 2	• Pin wedge to suit DTM04-08PA
DTM06-65	• 3	• 6 circuit DTM housing, takes sockets	WM85	• 2	 Socket wedge to suit DTM06-08SA
DTM04-08PA	• 2	• 8 circuit DTM housing, takes pins	WM12P	• 2	 Pin wedge to suit DTM04-12PA
DTM06-08SA	• 2	• 8 circuit DTM housing, takes sockets	WM12S	• 2	 Socket wedge to suit DTM06-12SA
DTM04-12PA	• 2	• 12 circuit DTM housing, takes pins	P20/1	• 100	• Male pin. Takes 2mm auto cable
DTM06-12SA	• 2	• 12 circuit DTM housing, takes sockets	S20/1	• 100	• Female pin. Takes 2mm auto cable
WM2P	• 10	• Pin wedge to suit DTM04-2P	SP20/1	• 50	• Sealing plug. Size 20
WM25	• 10	• Socket wedge to suit DTM06-25	TL2OR	• 1	• Blue removal tool. Size 20